



GRIZZLY BANDSAW COMPARISON CHART

| | G0457 | G0513 | G0513X2 | G0636X | G0514X | G0514X2 | G0514X3 | G0566 | G0531 | G0568 | G0569 |
|--|---|---|--|--|--|--|--|--|--|--|--|
| BANDSAW SIZE | 14" | 17" | 17" | 17" | 19" | 19" | 19" | 21" | 21" | 24" | 24" |
| THROAT CAPACITY (Left of Blade) | 13 ¹ / ₂ " | 16 ¹ / ₄ " | 16 ¹ / ₄ " | 16 ¹ / ₂ " | 18 ¹ / ₄ " | 18 ¹ / ₄ " | 18 ¹ / ₄ " | 20" | 20" | 24 ¹ / ₂ " | 24 ¹ / ₂ " |
| MAX. RESAW HEIGHT | 10" | 12" | 12" | 16" | 12" | 12" | 12" | 14 ¹ / ₈ " | 14 ¹ / ₈ " | 16 ¹ / ₄ " | 16 ¹ / ₄ " |
| MOTOR SIZE | 2 HP | 2 HP | 2 HP | 5 HP | 3 HP | 3 HP | 3 HP | 3 HP | 5 HP | 5 HP | 7 ¹ / ₂ HP |
| MOTOR VOLTAGE | 110/220V Single-Phase | 110/220V Single-Phase | 110/220V Single-Phase | 220V Single-Phase | 220V Single-Phase | 220V Single-Phase | 220/440V 3-Phase | 220V Single-Phase | 220V Single-Phase | 220V Single-Phase | 220/440V 3-Phase |
| RECOMMENDED CIRCUIT SIZE | 30/15 Amp | 30/15 Amp | 30/15 Amp | 30 Amp | 20 Amp | 20 Amp | 15/15 Amp | 20 Amp | 30 Amp | 30 Amp | 30/15 Amp |
| SWITCH TYPE | On/Off Push Button | On/Off Push Button | On/Off Push Button | Magnetic | Magnetic | Magnetic | Magnetic | Magnetic | Magnetic | Magnetic | Magnetic |
| BLADE CAPACITY | 1/8" - 3/4" | 1/8" - 1" | 1/8" - 1" | 1/8" - 1 ³ / ₈ " | 1/8" - 1 ¹ / ₄ " | 1/8" - 1 ¹ / ₄ " | 1/8" - 1 ¹ / ₄ " | 1/4" - 1 ³ / ₈ " | 1/4" - 1 ³ / ₈ " | 1/4" - 1 ¹ / ₂ " | 1/4" - 1 ¹ / ₂ " |
| BLADE LENGTH | 105 ³ / ₄ " - 107 ¹ / ₄ " | 131 ¹ / ₂ " | 131 ¹ / ₂ " | 160" - 162" | 143" | 143" | 143" | 165" | 165" | 181" | 181" |
| BLADE SPEED (FPM) | 3000 | 1700, 3500 | 1700, 3500 | 4500 | 1700, 3500 | 1700, 3500 | 1700, 3500 | 4600 | 4600 | 5300 | 5300 |
| BLADE GUIDES | Ball Bearings | Euro-Style Roller Disc | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings | Double Ball Bearings |
| BLADE RELEASE | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release | Quick Release |
| TABLE SIZE | 14 ³ / ₁₆ "W 19 ³ / ₄ "D | 17"W 17"D | 17 ¹ / ₄ "W 23 ⁵ / ₈ "D | 25 ¹ / ₂ "W 21"D | 19"W 26 ³ / ₄ "D | 19"W 26 ³ / ₄ "D | 19"W 26 ³ / ₄ "D | 29 ¹ / ₂ "W 20 ³ / ₄ "D | 29 ¹ / ₂ "W 20 ³ / ₄ "D | 33 ¹ / ₂ "W 23 ⁵ / ₈ "D | 33 ¹ / ₂ "W 23 ⁵ / ₈ "D |
| TABLE TYPE | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron |
| * GEARED TABLE RACK & PINION TILT * | No | No | No | Yes | No | Yes | Yes | Yes | Yes | Yes | Yes |
| TABLE TILT | 8° Left 45° Right | 10° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 5° Left 45° Right | 45° Right | 45° Right |
| TABLE TRUNNIONS | Aluminum | Steel | Cast Iron | Cast Iron | Steel | Cast Iron | Cast Iron | Cast Iron | Cast Iron | Cast Iron | Cast Iron |
| FENCE TYPE | Ground Cast Iron | Extruded Aluminum | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron | Ground Cast Iron |
| RESAW FENCE | Yes 6" Extruded | Not Included | Yes 6" Extruded | Yes 6" Extruded | Yes 6" Extruded | Yes 6" Extruded | Yes 6" Extruded | Not Included | Not Included | Not Included | Not Included |
| MITER GAUGE | Included | Included | Included | Included | Included | Included | Included | Included | Included | Included | Included |
| WHEELS | Balanced Cast Iron | Balanced Aluminum | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron | Balanced Cast Iron |
| BALL BEARING TYPE | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated | Shielded & Lubricated |
| DUST PORT(S) | 1 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" | 2 x 4" |
| FOOT BRAKE | No | No | No | Yes | No | Yes | Yes | Yes | Yes | Yes | Yes |
| FRAME TYPE | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel | Reinforced Steel |
| FLOOR-TO-TABLE HEIGHT | 42 ¹ / ₄ " | 37 ¹ / ₂ " | 37 ¹ / ₂ " | 35 ¹ / ₂ " | 37 ¹ / ₂ " | 37 ¹ / ₂ " | 37 ¹ / ₂ " | 35 ¹ / ₂ " | 35 ¹ / ₂ " | 34 ¹ / ₂ " | 34 ¹ / ₂ " |
| OVERALL HEIGHT | 73" | 73" | 73" | 78 ¹ / ₂ " | 76" | 76" | 76" | 78" | 78" | 83 ¹ / ₂ " | 83 ¹ / ₂ " |
| FOOT PRINT | 21 ¹ / ₂ " x 18 ¹ / ₄ " | 27" x 17 ³ / ₄ " | 27" x 17 ³ / ₄ " | 29 ¹ / ₂ " x 23 ¹ / ₂ " | 29 ¹ / ₂ " x 17 ³ / ₄ " | 29 ¹ / ₂ " x 17 ³ / ₄ " | 29 ¹ / ₂ " x 17 ³ / ₄ " | 21 ⁵ / ₈ " x 33 ¹ / ₂ " | 21 ⁵ / ₈ " x 33 ¹ / ₂ " | 41 ³ / ₈ " x 23 ¹ / ₂ " | 41 ³ / ₈ " x 23 ¹ / ₂ " |
| MACHINE WEIGHT | 198 lbs | 266 lbs | 352 lbs | 620 lbs | 383 lbs | 427 lbs | 427 lbs | 581 lbs | 594 lbs | 836 lbs | 847 lbs |
| SHIPPING WEIGHT | 214 lbs | 342 lbs | 418 lbs | 675 lbs | 418 lbs | 480 lbs | 456 lbs | 684 lbs | 667 lbs | 951 lbs | 962 lbs |
| COUNTRY OF ORIGIN | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan | Taiwan |
| 2008 CATALOG PRICE | \$825.00 | \$750.00 | \$950.00 | \$1,995.00 | \$1,150.00 | \$1,295.00 | \$1,295.00 | \$1,850.00 | \$1,895.00 | \$2,595.00 | \$2,595.00 |



HEAVY-DUTY DOUBLE BALL BEARING BLADE GUIDES

DELUXE RE-SAW FENCE INCLUDED



BALANCED CAST IRON WHEELS



*** GEARED TABLE RACK & PINION TILT ***

